

RotoTank™

Manufactures of Water, Chemical, Transport, Septic Tanks and Silos

TOUGH, FLEXIBLE, ECONOMICAL AND EXTREMELY RELIABLE PLASTIC TANKS:

Getting the best out of your Rotational Moulded Polyethylene RotoTank™ tanks

Place your RotoTank™ tank on a flat level surface.

- A solid wooden platform, smooth concrete plinth or smooth level bed of river sand is best.

Increase the tank's useful life by reducing the direct hours of sunlight to which the RotoTank tank is exposed.

- All RotoTank™ tank products are manufactured using UV Stabilised LLDPE resin. However, the tank's life span can further be extended by positioning the RotoTank™ tank in the shade of trees, under a lean-to, on the South side of a building or under shade cloth as a means to protect your RotoTank™ tank from excessive sunlight (UV rays).

Avoid mechanical damage by:

- Not lifting the RotoTank™ tank while it still has liquid in it.
- Ensuring that hot exhaust gases do not impinge directly onto the RotoTank™ tank and hot exhaust pipes do not touch the RotoTank™ tank.
- Ensuring that the RotoTank™ tank is not unnecessarily dropped and especially not onto its corners.
- Ensuring that high stress loads are not applied to the RotoTank™ tank by lifting equipment or "tie-down" securing straps and ropes. Avoid the use of steel cables and wire for this purpose.
- Storing only products that are compatible with the grade of Linear Low Density Polyethylene used for manufacturing your RotoTank™ tank. If in doubt, contact RotoTank™ for more advice.

Reduce the temperatures to which the RotoTanks™ are exposed by:

- Clearing the area around your RotoTank™ tank to prevent fire damage.
- Not storing hot products (above 80° C) in your RotoTank™ tank for long periods of time. The RotoTank™ tank can however be steam cleaned with atmospheric steam.
- Keeping the RotoTank™ tank full of water when it is not being used for storing other liquids reduces the surface temperatures of the plastic and extends its life.

TANK TYPES:	a) Water SG 1.0	b) Medium SG 1.4	c) Heavy SG 1.6	d) Extra heavy SG 1.8
-------------	--------------------	---------------------	--------------------	--------------------------

SIZES:	Length mm	Width mm	Height mm	Lid mm
220 lt Water	835	635	610	180
220 lt Planter	1050	640	610	180
250 lt Planter	1040	645	610	180
500 lt	1140	840	725	180
600 lt	1200	860	980	180
1000 lt	1700	1 100	950	450
2500 lt	2 150	1 500	1 280	450
5000 lt	2 500	2 100	1 500	450
6000 lt	2 200	2 550	1 500	450
8000 lt	4 150	1 850	1 960	450



Produced in conjunction with the Association of Rotational Moulders of South Africa - committed to the use of quality Polyethylene rotomoulded products.



Horizontal Tanks

Gauteng Sales: Tel: +27 12 376 1070/2, E-mail: sales@rototank.co.za; info@rototank.co.za

Cape Sales: +27 22 715 3069, E-mail: capesales@rototank.co.za

KZN Sales: +27 39 685 7243, E-mail: kznsales@rototank.co.za

www.rototank.co.za 086 000 TANK (8265)